

Mongoose[™] **Electric Powered Chemical Metering Pumps**





MJ Systems, LLC Authorized Graco Distributors TX - Off (281) 842-7600 LA - Off (225) 726-7114 SYSTEMS www.mjsusa.com • sales@mjsusa.com

PROVEN QUALITY. LEADING TECHNOLOGY.

Mongoose Electronic Low Pressure Chemical Metering Pump

Our Mongoose series metering pump is suitable for dispensing chemicals for a variety of diverse markets such as oil and natural gas, mining, agriculture, landscaping and lawn maintenance, waste water, and car wash. These pumps can also be used in chemical dosing maintenance applications including cooling towers, boilers, and plating, as well as a multitude of other uses.

Graco check valves

- Proprietary design (SST Head)
- Poppet style eliminates valve from sticking
- Same style valve used on other Graco chemical pumps

Thermal overload protection

- Prevents overcurrent and overheating
- Easily replaceable
- No longer a throwaway pump

Prime/air bleed port

- No need to remove fluid section to prime pump
- · Quick and easy

Other features

- Manual stroke adjustment
- Splash cover over controls
- NEMA 4x style enclosure
- UL and CSA certified



Mongoose SST Head



Mongoose Graco Check Valve on SST models



Mongoose PVDF Head


Ordering Information

Mongoose Chemical Metering Pump Model Numbers									
Part Number	Description*	Flow	Flow Pressure		Fluid Section				
A21000	LCI-1A17-SPD-0	17 gpd (64.3 lpd)	250 psi (17.2 bar)	120 VAC	316 SST				
A21004	LCI-2A17-SPD-0	17 gpd (64.3 lpd)	250 psi (17.2 bar)	240 VAC	316 SST				
A21016	LCI-1210-SPD-0	10 gpd (37.8 lpd)	140 psi (9.6 bar)	12 VDC	316 SST				
A21008	LCI-1A17-KPA-0	17 gpd (64.3 lpd)	250 psi (17.2 bar)	120 VAC	PVDF				
A21009	LCI-1A15-KPA-0	15 gpd (56.7 lpd)	150 psi (10.3 bar)	120 VAC	PVDF				
A21010	LCI-1A30-KPA-0	30 gpd (113.5 lpd)	110 psi (7.5 bar)	120 VAC	PVDF				
A21011	LCI-1A45-KPA-0	45 gpd (170.3 lpd)	75 psi (5.2 bar)	120 VAC	PVDF				
A21012	LCI-2A17-KPA-0	17 gpd (64.3 lpd)	250 psi (17.2 bar)	240 VAC	PVDF				
A21013	LCI-2A15-KPA-0	15 gpd (56.7 lpd)	150 psi (10.3 bar)	240 VAC	PVDF				
A21014	LCI-2A30-KPA-0	30 gpd (113.5 lpd)	110 psi (7.5 bar)	240 VAC	PVDF				
A21015	LCI-2A45-KPA-0	45 gpd (170.3 lpd)	75 psi (5.2 bar)	240 VAC	PVDF				

Technical Data

Mongoose Chemical Metering Pump								
Maximum fluid working pressure	250 psi (17.2 bar)							
Cycle rate	125 - 145 cpm							
Input Voltage	120 VAC, 240 VAC, 12 VDC							
Amperage Max Load	0.1 - 0.5 A							
Frequency	50/60 Hz							
Environmental temperature range	-40° to 120°F (-40° to 50°C)							
Inlet/Outlet Sizes								
Fluid inlet size	1/4 in. npt, 1/4 tube, 3/8 tube							
Fluid outlet size (1/4" plungers only)	1/4 in. npt, 1/4 tube, 3/8 tube							
Prime/bleed size (1/4" plungers only)	1/16 in. npt, tube connection							
Wetted Parts								
Pump/Diaphragm Seal Material	PEEK and PTFE unless otherwise noted							
Other	316 stainless steel or PVDF							
Check Valve Seal Material	FFKM or FKM							
Weight								
All models	9.0 to 10.0 lb (4.0 to 4.5 kg)							

Dimensions



Configuration Number Matrix

Check the identification plate (ID) for the 11-digit Configuration Number of your pump. Use the following matrix to define the components of your pump. *NOTE: Not all combinations are possible.*

Samp	le Configu	ration	Number:	LC	<u>-1A15-SP</u>	D-C)						
	V										•		•
	LCI Low Pressure		1A Voltage	15 Pump Performance		S Pump Material		P Diaphragm		D Check Valve		0 Options	
	Chemical Injection		Voltage	T ump T enormance				Material		Seal Material		Options	
Low Pressure Motor Size		Voltage		Pump Performance		Pump Material		Diaphragm Material		Check Valve Seal Material		Options	
350	3-1/2"	12	12 VOC	10	10 gpd (37.8 lpd) 140 psi (9.6 bar)	S	316 SST	Р	PTFE Coated	D	FFKM	0	None
		1A	120 VAC	15	15 gpd (56.7 lpd) 150 psi (10.3 bar)	К	PVDF			Α	FKM		
		2A	240 VAC	17	17 gpd (64.3 lpd) 250 psi (17.2 bar)								
				30	30 gpd (113.5 lpd) 110 psi (7.5 bar)								
				45	45 gpd (170.3 lpd) 75 psi (5.2 bar)								



ABOUT GRACO | PROVEN QUALITY. LEADING TECHNOLOGY.

Founded in 1926, Graco is a world leader in fluid handling systems and components. Graco products move, measure, control, dispense and apply a wide range of fluids and viscous materials used in vehicle lubrication, commercial and industrial settings.

The company's success is based on its unwavering commitment to technical excellence, world-class manufacturing and unparalleled customer service. Working closely with qualified distributors, Graco offers systems, products and technology that set the quality standard in a wide range of fluid handling solutions. Graco provides equipment for spray finishing, protective coating, paint circulation, lubrication, and dispensing sealants and adhesives, along with power application equipment for the contractor industry. Graco's ongoing investment in fluid management and control will continue to provide innovative solutions to a diverse global market.

GRACO LOCATIONS

MAILING ADDRESS

P.O. Box 1441 Minneapolis, MN 55440-1441 Tel: 612-623-6000 Fax: 612-623-6777

AMERICAS

MINNESOTA Worldwide Headquarters Graco Inc. 88-11th Avenue N.E. Minneapolis, MN 55413

EUROPE

BELGIUM European Headquarters Graco N.V. Industrieterrein-Oude Bunders Slakweidestraat 31 3630 Maasmechelen, Belgium Tel: 32 89 770 700 Fax: 32 89 770 777

ASIA PACIFIC

AUSTRALIA

Graco Australia Pty Ltd. Suite 17, 2 Enterprise Drive Bundoora, Victoria 3083 Australia Tel: 61 3 9467 8558 Fax: 61 3 9467 8559

CHINA

Graco Hong Kong Ltd. Shanghai Representative Office Room 118 1st Floor No.2 Xin Yuan Building No.509 Cao Bao Road Shanghai, 200233 The People's Republic of China Tel: 86 21 649 50088 Fax: 86 21 649 50077

INDIA

Graco Hong Kong Ltd. India Liaison Office Room 432, Augusta Point Regus Business Centre 53 Golf Course Road Gurgaon, Haryana India 122001 Tel: 91 124 435 4208 Fax: 91 124 435 4001

JAPAN

Graco K.K. 1-27-12 Hayabuchi Tsuzuki-ku Yokohama City, Japan 2240025 Tel: 81 45 593 7300 Fax: 81 45 593 7301

KOREA

Graco Korea Inc. Shinhan Bank Building 4th Floor #1599 Gwanyang-Dong, Dongan-Ku, Anyang-si, Korea 431-060 Tel: 82 31 476 9400 Fax: 82 31 476 9801

SALES/ DISTRIBUTION/ SERVICE

Call today for product information or to request a demonstration: 866.552.1868 or visit www.graco.com/ong

Graco Inc. is registered to I.S. EN ISO 9001



MJ Systems, LLC Authorized Graco Distributors TX - Off (281) 842-7600 LA - Off (225) 726-7114 www.mjsusa.com • sales@mjsusa.com

North America Customer Service 866-552-1868

©2016 Graco Inc. 3G0030 Rev. A 06/16 Printed in the U.S.A. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice. All other brand names or marks are used for identification purposes and are trademarks of their respective owners.